

MORE FROM LESS



ADVANCED
FIREFIGHTING
TECHNOLOGY



AFT TROLLEY 50/02

- ▶ LOW PRESSURE
- ▶ WATER MIST/CAFS
- ▶ HIGH EFFICIENCY
- ▶ RIDABLE & MOBILE

www.aftwatermist.com

TECHNICAL SPECIFICATIONS		TROLLEY 50/02
Extinguishing agent tank		
Filling capacity as per EN 1866	50 litres	
Material	Stainless steel	
Working pressure		
Pressure at pressure reducer	8,5 bar	
Propellant gas bottle		
Medium	Compressed air	
Technical specifications of pressure cylinder	<ul style="list-style-type: none"> • Filling pressure: 300 bar • Volume: 6 litres • Valve connection: G5/8 interior 	
Technical Parameters		
Operating time	Approx. 125 sec.	
Flow rate	24 litres/min	
Operating temperature	Tmin + 5°C; Tmax + 60°C	
Trolley Frame	Double powder coated steel frame	
Extinguishing gun		
Changeover time	Approx. 2 sec. from jet to spray mode	
Lancing distance	Approx. 16 - 18 m jet mode Approx. 6 - 7 m spray mode	
Electrical Fires	Up to 1000 V / 3 m distance	
Hose lengths	5 m, 10 m, 15 m	
Ratings (using Ecodare 423)		
Fire Class A and B	IVB (as per EN 1866)	
Dimensions		
Weight empty (without air bottle)	Approx. 52 kg	
Dimensions (LxWxH)	Approx. 620 x 540 x 1110 mm	
Certifications		
Standards	DIN EN 1866, GS, SOLAS, TÜV, ISO 9001 (manufacturer)*	

* Country and sector-specific regulations have higher priority. If you have any questions, please contact AFT GmbH.



- “MADE IN GERMANY”
- JET AND SPRAY MODE
- EASY TO OPERATE
- SUITABLE FOR MANY EXTINGUISHING AGENTS
- CONSISTENT WATER MIST SPRAY
- V4A STAINLESS STEEL CONTAINER
- EASY TO MOVE
- EASY TO FILL
- LOW WORKING PRESSURE
- CERTIFICATION IN ACCORDANCE WITH EN 1866